# MPI002/28/RD Datasheet



## Product Name // Stainless Steel Vandal Resistant Illuminated IP66 Push Button Switch MPI002 Series Red LED Ring (No Resistor) 2.8mm Tab Termination

View Product Page



hage not found or type unknown

#### // Product Description:

- 0 Stainless Steel Illuminated Vandal Resistant Push Button Switches
- 0 22mm diameter
- O Single Contact, push to make, tactile (momentary action)
- 0 Choice of Termination, depending on part code:
- 0 /28 - 2.8mm Tab
- 0 /TE or /TERM - Screw Terminal
- 0 /RP - Solder Tag
- 0 /FL - 300mm Flying Leads; white - switch, red - LED +, black -
- 0 Choice of Illumination style depending on part code:
- 0 Part codes prefixed MPI001 - Centre dot

- O Part codes prefixed MPI002 Ring
- 0 Choice of LED colour depending on part code:
- Single colour: /RD Red, /GN Green, /AM Amber, /BL Blue, /WH - White
- 0 Dual colour (only available in /28 2.8mm Tab and /TE Screw Terminal versions): /D1 - Red/Green, /D4 - Red/Blue, /D5 -
- 0 (When dual colour LEDs are forward biased the first colour is lit, when reverse biased the second colour is list)
- Choice of LED operating voltage depending on part code suffix:
- Resistor installed for operation at a single fixed voltage: /6 6V DC, /12 - 12V DC, /24 - 24V DC
- O Also available with no resistor installed (no suffix) see data for ratings to enable calculation of suitable series resistor value for application
- Front panel seal to IP66 (microswitch not sealed). /RP Solder Tag versions are also rear panel sealed to IP66

### **General Information:**

**Product Display Title:** 

**Product Family: Product Series:** 

**Body Material:** 

**Current Max:** 

Diameter:

Function:

Illumination Colour:

Illumination Shape: Illumination Style: Illumination Voltage:

Ip Rating:

**Max Operating Temperature:** 

Min Operating Temperature:

Thread Size: Voltage Max: Stainless Steel Illuminated Vandal Resistant Push Button Switches

Switches Push Button

SS 304

0.05A

22mm

Momentary Action

Red

Ring Illuminated

No Resistor

IP66

+70°C

-30°C

0.747 inch x 26TPI

24V

#### // Product PDF Links



#### // Product 3D CAD Model Links

