
## **PX0100S08AGY Datasheet**



# Product Name // 8 Contacts Male Standard Rectangular Grey Connector

View Product Page





#### // Product Description:

- O 8 Contacts Male Standard Rectangular Grey Connector
- Enhanced Seal Protection (ESR), Protective End Cap (PEC), Terminating Resistor (TER), Shrink Boot Adapter (SBA), Welded Flange (WFL) and Y-Type Connector (YTY) Available
- Water and dustproof to IP68 when mated with compatible connector
- Mate with PX0101 Series, as appropriate

- O Wedgelocks provided
- O Crimp Terminals
- O Mechanical Cycles = 100 (min)
- Operating Temperature = -25°C to +120°C

#### // General Information:

**Product Display Title:** 

Product Family:

Product Series: Body Colour:

Body Material:

**Body Material Type:** 

Contact Type:

Coupling Type: Current Max:

Ip Rating:

Max Operating Temperature: Min Operating Temperature:

Number Of Contacts: Voltage Max: 8 Contacts Male Standard Rectangular Grey Connector

Rectangular Connectors

Standard Rectangular Connectors

Grey

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body

Socket Contact Snap-in

13A

IP68

+120°C

-40°C

8 Contacts

250V

### // Product PDF Links



// Product 3D CAD Model Links

