Interconnect Solutions



121587-0026

Part Number Details

Global Mfg Part No.	121587-0026	
series	TSTRECT	
category	Trident	
line	Trident	
brand	Cannon	
ittPartNo	TFR36AH10	

Series		Trident Flame Retardant Rectangular		
Operating Voltage		Up to 250 V ac rms		
Contact Current Rating		Up to 13 A		
Operating Temperature		-55°C to +105°C		
Insulation Resistance		5000 Megaohms at 500 V dc		
Durability		Up to 500 Mating Cycles		
Flammability Rating		UL94-V0		
Number of Contacts		36		
Туре		Accessory: Plug Strain Relief Hood		
Contact Type		No Contacts delivered, please order separately.		
Colour		Insulator: Grey Polyamid for Railway Applications		
· · · ·	material restrictions of lead, cadmium, hexavalent chromium, mercury, poly bromated biphenyl ether (PBB) and poly bromide diphenyl ether (PBDE) according to directive 2011/65/EU			
rohsCompliantFlag	YES			

A datasheet is available for download.

Download Datasheet PDF

Check the stock availability of this product at our distributors.

Check Stock Now

Part Number	Distributor	Qty	Location
121587-0026	Master Electronics	34	United States

30 United States

Note: Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS. ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Contact Us" at the top of every page.

globalManufPartNo: 121587-0026; line: Trident; ittPartNo: TFR36AH10 Request a Quote